

Our material compositions are as individual as your requirements. The ideal composition of polyurethane, resin or rubber with the corresponding grain guarantees the perfect result. Regardless of whether initial equipment, tools with a long service life, economic variants or special glass: you decide what you need, we have the matching series.

SERIE BK - WN1

Pumice and aluminium oxide in a special rubber bond produce a good industrial gloss at an economic price.

EDGE PROFILES



Flat glass and arris

Gehrung 45°

Facette

Laminated safety glass (LSG)

MACHINES

Single and double edger machines

TOOL

Product : ARTIFEX BK - WN1
 Bonding : Rubber | vulcanised
 Grain : Pumice, Aluminium oxide
 46 | 60 | 80 | 120 | 180
 Hardness : Soft elastic
 Colour : Brown | Yellow
 Delivery form : Cup wheels with plate
 Full material cup wheels
 Peripheral wheels
 Dimension : Ø 130 - 200 mm

RESULT

Good industrial gloss

ADVANTAGE

Low tool costs

LSG

We offer this product series segmented with 3-mm or 5-mm slots for perfect laminated glass processing. Your advantage: no clogging of the cup wheels, no sticking of foil on the glass edges. This is how easy it is to process laminated glass.



PRODUCT CODE EXAMPLE

Bonding : _____
 Hardness : _____
 Grain : _____
 Type of grain : _____
 ARTICLE : BK 46 W N1

The ARTIFEX promise

We stand for tools that guarantee the highest quality standards. All ARTIFEX products are „Made in Germany“ and their above-average service life speaks for itself.

Our service: You have individual requirements, we offer customised solutions regardless of the material, shape or dimensions. We will gladly advise you on your premises.